



APC Smart-UPS RT 10kVA, 230/400V, 4x IEC 60320 C13 & 6x IEC Jumpers & 4x IEC 60320 C19 outlets

SURT10000XLI

! Discontinued

- ! To be discontinued on: 1 Oct 2025
- ! To be end-of-service on: 31 Dec 2025

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main	
Main Input Voltage	230 V
	400 V 3 phases
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V
	240 V
Main Output Voltage	230 V
Other Output Voltage	220 V
	240 V
Rated power in W	8000 W
Rated power in VA	10000 VA
output connection type	4 IEC 60320 C13
	6 IEC Jumpers
	4 IEC 60320 C19
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	6U
Provided equipment	CD with software
	Service manual
	Smart UPS signalling RS-232 cable
	User manual
	Web/SNMP management card
Range of product	Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery type	Lead-acid battery
Extended runtime	1
Number of battery filled slots	4
Number of battery free slots	0

Battery recharge time	2 h
Number of battery replacement quantity	2
Battery life	35 year(s)
Replacement battery	APCRBC140 ☐
Battery charger power	955 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
UPS type	Double conversion online

Physical

_	
Colour	Black
Height	432 mm
Width	263 mm
Depth	736 mm
Net weight	110.91 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Input harmonic distortion	Less than 7 % for full load
Input voltage limits	160280 V
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Network frequency	50/60 Hz +/- 5 Hz auto-sensing

Output

Bypass type	Internal bypass (automatic and manual)
Crest factor	3:1
Harmonic distortion	Less than 3 %
Maximum configurable power in VA	10000 VA
Maximum configurable power in W	8000 W
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	55 dBA
Heat dissipation	2262 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	015240 m
IP degree of protection	IP20
Relative humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

Communications & Management

Emergency power off	Yes
Free slots	0
Preinstalled device	Network management card 2 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	1265 J
Noise suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	59.000 cm
Package 1 Width	60.000 cm
Package 1 Length	98.000 cm
Package 1 Weight	139.989 kg

Contractual warranty

Warranty	2 years renair or replace	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	28130
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8
REACh Regulation	REACh Declaration
Energy Efficiency Optimized	Energy efficient product

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

