



(!) Discontinued

APC Smart-UPS RT 3000VA, 230V, 8x IEC 60320 C13 & 3x IEC Jumpers & 2x IEC 60320 C19 outlets

SURT3000XLI

Discontinued on: May 31, 2023

Overview

Lead time	Usually in Stock
Main	
Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2100 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
output connection type	8 IEC 60320 C13 3 IEC Jumpers 2 IEC 60320 C19
Number of rack unit	3U
Cable length	2.4 m
Number of cables	1
Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Run Time	View Runtime Graph ☐
Battery type	Lead-acid battery
Extended runtime	1
Number of battery filled slots	2
Battery recharge time	2.5 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC140 ☐
Battery charger power	382 W rated

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
UPS type	Double conversion online

Physical

Colour	Black
Height	43.2 cm
Width	13 cm
Depth	66 cm
Net weight	54.56 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Input voltage limits	160280 V
Network frequency	50/60 Hz +/- 5 Hz auto-sensing

Output

Bypass type	Internal bypass (automatic and manual)
Crest factor	3:1
Harmonic distortion	Less than 3 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
Wave type	Sine wave
Efficiency	91 % (full load)
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product certifications	BSMI C-Tick CE	
	CSA	
	GOST	
	JEON	
	VCCI	
	VDE	

Environmental

Heat dissipation	655 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	015240 m
Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.7 cm
Package 1 Width	98 cm
Package 1 Length	60.3 cm
Package 1 Weight	63.64 kg

Contractual warranty

Warranty	2 years repair or replace	
----------	---------------------------	--



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

W Energy efficiency

Energy Efficiency Optimized Energy efficient product

Use Again

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	